SAFETY DATA SHEET UNIPART SCREENWASH CONCENTRATE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name UNIPART SCREENWASH CONCENTRATE

DUCDCC 49, DUCDCC 42, GEM1225, USW5, USW1 Product number

Internal identification B18905, 18602, 18605, 18700, 18615, 18620

Container size 500ML BOTTLES TO 25 LITRE DRUMS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses All purpose automotive windscreen cleaner

Uses advised against This product is not recommended for any industrial, professional or consumer use other than

the identified uses stated above.

1.3. Details of the supplier of the safety data sheet

Supplier **Unipart Autoparts**

> Unipart House, Garsington Road,

Cowley, Oxford, OX4 2PG 02476 466 461

customer.support@unipartautoparts.com

1.4. Emergency telephone number

Emergency telephone Tel:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 3 - H226

Acute Tox. 4 - H302 STOT SE 1 - H370 Health hazards

Environmental hazards Not Classified

Classification (67/548/EEC or T;R39/23/24/25. Xn;R20/21/22. R10.

1999/45/EC)

2.2. Label elements

Pictogram







Signal word

Hazard statements H226 Flammable liquid and vapour.

> H302 Harmful if swallowed. H370 Causes damage to organs .

UNIPART SCREENWASH CONCENTRATE

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe vapour/spray.

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor.

P321 Specific treatment (see medical advice on this label).

P330 Rinse mouth.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

P102 Keep out of reach of children.

Contains METHANOL, ETHANEDIOL

Detergent labelling < 5% perfumes, Contains BENZISOTHIAZOLINONE

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

METHANOL		10-30%	
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01- 2119433307-44-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Flam. Liq. 2 - H225	F;R11 T;R2	3/24/25,R39/23/24/25	
Acute Tox. 3 - H301			
Acute Tox. 3 - H311			
Acute Tox. 3 - H331			
STOT SE 1 - H370			

ETHANEDIOL			1-5%
CAS number: 107-21-1	EC number: 203-473-3	REACH registration number: 01-2119456816-28-XXXX	
Classification	Classification (67/548/EEC or 1999/45/EC)		
Acute Tox. 4 - H302 STOT RE 2 - H373	Xn;R22		

UNIPART SCREENWASH CONCENTRATE

PROPYLENE GLYCOL <1%

CAS number: 57-55-6 EC number: 200-338-0 REACH registration number: 01-

2119456809-23-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

2.6-DIMETHYL-7-OCTEN-2-OL <1%

CAS number: 18479-58-8 EC number: 242-362-4 REACH registration number: 01-

2119457274-37-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Irrit. 2 - H315 Xi;R36/38.

Eye Irrit. 2 - H319

SODIUM HYDROXIDE <1%

CAS number: 1310-73-2 EC number: 215-185-5 REACH registration number: 01-

2119457892-27-XXXX

Classification Classification (67/548/EEC or 1999/45/EC)

Met. Corr. 1 - H290 C;R35

Skin Corr. 1A - H314 Eye Dam. 1 - H318

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.,The product contains organic

solvents.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Never give anything by mouth to an unconscious person. Get medical attention if

any discomfort continues.

Inhalation Remove affected person from source of contamination. Keep affected person away from heat,

sparks and flames. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Ingestion Do not induce vomiting. Rinse mouth thoroughly with water. Move affected person to fresh air

and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention immediately.

Skin contact Remove affected person from source of contamination. Immediately remove contaminated

clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if

symptoms occur after washing.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any

discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

In the unlikely event of over exposure to organic solvent vapours from this product, symptoms

which may develop include headache, fatigue, dizziness and nausea.

Ingestion May cause unconsciousness, blindness and possibly death.

Skin contact Skin irritation.

Eye contact May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following

media: Alcohol-resistant foam. Carbon dioxide (CO2). Water spray, fog or mist. Dry

chemicals, sand, dolomite etc.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

May explode when heated or when exposed to flames or sparks. Solvent vapours may form explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. May form explosive or toxic mixtures with air. Vapour explosion and poison hazard

indoors, outdoors and in sewers.

Hazardous combustion

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters

Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces. Take precautionary measures against static discharges. No smoking, sparks, flames or other

sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Stop leak if possible without risk. DO NOT touch spilled material! Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Cover large spillages with alcohol-resistant foam. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Avoid spilling. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. During application and drying, solvent vapours will be emitted. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from oxidising materials, heat and flames. May attack some plastics, rubber and coatings. Take precautionary measures against static discharges.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³
Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³
Long-term exposure limit (8-hour TWA): 2006/15/EC 200 ppm 260 mg/m³
Sk

ETHANEDIOL

Long-term exposure limit (8-hour TWA): WEL 52 mg/m³ 20 ppm

Short-term exposure limit (15-minute): WEL 104 mg/m3 40 ppm vapour

Sk

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

PROPYLENE GLYCOL

Long-term exposure limit (8-hour TWA): WEL 474 mg/m3 150 ppm particulate vapour Long-term exposure limit (8-hour TWA): WEL 10 mg/m3 particulate

2,6-DIMETHYL-7-OCTEN-2-OL

No exposure limit value known.

SODIUM HYDROXIDE

Short-term exposure limit (15-minute): WEL 2 mg/m³

WEL = Workplace Exposure Limit Sk = Can be absorbed through skin. Sk = Can be absorbed through the skin.

METHANOL (CAS: 67-56-1)

DNEL Industry - Dermal; Short term Acute: 40 mg/kg bw/day

Industry - Dermal; Long term systemic effects: 40 mg/kg bw/day

Industry - Inhalation; Short term Acute: 260 mg/m³

Industry - Inhalation; Long term systemic effects: 260 mg/m³ Consumer - Dermal; Short term Acute: 8 mg/kg bw/day

Consumer - Dermal; Long term systemic effects: 8 mg/kg bw/day Consumer - Inhalation; Long term systemic effects: 50 mg/m³

Industry - Inhalation; Short term Acute: 260 mg/m³ Industry - Inhalation; Long term local effects: 260 mg/m³ Consumer - Inhalation; Short term Acute: 50 mg/m³ Consumer - Inhalation; Long term local effects: 50 mg/m³

PNEC - Fresh water; 20.8 mg/l

Marine water; 2.08 mg/lSoil; 3.18 mg/kg soil dw

- STP; 100 mg/l

- Sediment (Freshwater); 77 mg/kg sediment dw

- Intermittent release; 1540 mg/l

- Sediment (Marinewater); 7.7 mg/kg sediment dw

ETHANEDIOL (CAS: 107-21-1)

DNEL Industry - Dermal; Long term systemic effects: 106 mg/kg bw/day

Industry - Inhalation; Long term local effects: 35 mg/m³

Consumer - Dermal; Long term systemic effects: 53 mg/kg bw/day

Consumer - Inhalation; Long term local effects: 7 mg/m³

PNEC - Fresh water; 10 mg/l

- Marine water; 1 mg/l

- Sediment (Freshwater); 37 mg/kg sediment dw

- Intermittent release; 10 mg/l

Soil; 1.53 mg/kgSTP; 199.5 mg/l

- Sediment (Marinewater); 3.7 mg/kg sediment dw

- Soil; 1.53 mg/kg soil dw

FATTY ALCOHOL ALKOXYLATE 4 (CAS: 111905-53-4)

DNEL No DNEL available.

PNEC

No PNEC available.

PROPYLENE GLYCOL (CAS: 57-55-6)

DNEL Industry - Inhalation; Long term systemic effects: 168 mg/m³

Industry - Inhalation; Long term local effects: 10 mg/m³
Consumer - Inhalation; Long term systemic effects: 50 mg/m³
Consumer - Inhalation; Long term local effects: 10 mg/m³

UNIPART SCREENWASH CONCENTRATE

PNEC - Fresh water; 260 mg/l

- Marine water; 26 mg/l- STP; 20000 mg/kg

Sediment (Freshwater); 572 mg/kgSediment (Marinewater); 57.2 mg/kg

- Soil; 50 mg/kg

- Intermittent release; 183 mg/l

2,6-DIMETHYL-7-OCTEN-2-OL (CAS: 18479-58-8)

DNEL Workers - Inhalation; Long term systemic effects: 73.5 mg/m³

Workers - Dermal; Long term systemic effects: 20.8 mg/kg bw/day General population - Inhalation; Long term systemic effects: 21.7 mg/m³

General population - Dermal, Oral; Long term systemic effects: 12.5 mg/kg bw/day

PNEC - Fresh water; 0.0278 mg/l

Marine water; 0.00278 mg/lIntermittent release; 0.278 mg/l

- STP; 10 mg/l

Sediment (Freshwater); 0.594 mg/kg sediment dwSediment (Marinewater); 0.0594 mg/kg sediment dw

- Soil; 0.103 mg/kg soil dw

3,7-DIMETHYL-1,6-OCTADIEN-3-OL (CAS: 78-70-6)

DNEL Workers - Inhalation; Long term systemic effects: 2.8 mg/m³

Workers - Inhalation; Short term Acute: 16.5 mg/m³

Workers - Dermal; Long term systemic effects: 2.5 mg/kg bw/day

Workers - Dermal; Short term Acute: 5 mg/kg bw/day Workers - Dermal; Long term local effects: 15 mg/cm² Workers - Dermal; Short term Acute: 15 mg/cm²

General population - Inhalation; Long term systemic effects: 0.7 mg/m3

General population - Inhalation; Short term Acute: 4.1 mg/m³

General population - Dermal; Long term systemic effects: 1.25 mg/kg bw/day

General population - Dermal; Short term Acute: 2.5 mg/kg bw/day General population - Dermal; Long term local effects: 15 mg/cm² General population - Dermal; Short term Acute: 15 mg/cm²

General population - Oral; Long term systemic effects: 0.2 mg/kg bw/day

General population - Oral; Short term Acute: 1.2 mg/kg bw/day

- Fresh water; 0.2 mg/l

Marine water; 0.02 mg/lIntermittent release; 2 mg/l

- STP; 10 mg/l

PNEC

Sediment (Freshwater); 2.22 mg/kg sediment dwSediment (Marinewater); 0.222 mg/kg sediment dw

- Soil; 0.327 mg/kg soil dw

CITRAL (CAS: 5392-40-5)

7/21

UNIPART SCREENWASH CONCENTRATE

DNEL Workers - Inhalation; Long term systemic effects: 9 mg/m³

Workers - Dermal; Long term systemic effects: 1.7 mg/kg bw/day

Workers - Dermal; Long term local effects: 0.14 mg/cm²

General population - Inhalation; Long term systemic effects: 2.7 mg/m³ General population - Dermal; Long term systemic effects: 1 mg/kg bw/day General population - Dermal; Long term local effects: 0.14 mg/cm²

General population - Oral; Long term systemic effects: 0.6 mg/kg bw/day

PNEC - Fresh water; 0.00678 mg/l

Marine water; 0.000678 mg/lIntermittent release; 0.0678 mg/l

- STP; 1.6 mg/l

Sediment (Freshwater); 0.125 mg/kg sediment dw
Sediment (Marinewater); 0.0125 mg/kg sediment dw

- Soil; 0.0209 mg/kg soil dw

SODIUM HYDROXIDE (CAS: 1310-73-2)

DNEL Consumer - Inhalation; local effects: 1 mg/m³

Industry - Inhalation; Long term local effects: 1 mg/m³

d-LIMONENE (CAS: 5989-27-5)

DNEL Workers - Inhalation; Long term systemic effects: 33.3 mg/m³

Workers - Dermal; Short term local effects, Acute: 0.222 mg/cm²

General population - Inhalation; Long term systemic effects: 8.33 mg/m³ General population - Dermal; Short term local effects, Acute: 0.111 mg/cm² General population - Oral; Long term systemic effects: 4.76 mg/kg bw/day

PNEC - Fresh water; 0.0054 mg/l

- Marine water; 0.00054 mg/l

- STP; 1.8 mg/l

- Sediment (Freshwater); 1.32 mg/kg sediment dw

- Marine water; 0.13 mg/kg sediment dw

- Soil; 0.262 mg/kg soil dw

GERANIOL (CAS: 106-24-1)

DNEL Workers - Inhalation; Long term systemic effects: 161.6 mg/m³

Workers - Dermal; Long term systemic effects: 12.5 mg/kg bw/day

Workers - Dermal; Long term local effects: 11.8 mg/cm²

General population - Inhalation; Long term systemic effects: 47.8 mg/m³ General population - Dermal; Long term systemic effects: 7.5 mg/kg bw/day

General population - Dermal; Long term local effects: 11.8 mg/cm²

General population - Oral; Long term systemic effects: 13.75 mg/kg bw/day

PNEC - Fresh water; 0.0108 mg/l

- Marine water; 0.00108 mg/l

- Intermittent release; 0.108 mg/l

- STP; 0.7 mg/l

Sediment (Freshwater); 0.115 mg/kgSediment (Marinewater); 0.0115 mg/kg

- Soil; 0.0167 mg/kg

BUTYLPHENYL METHYLPROPIONAL (CAS: 80-54-6)

8/21

UNIPART SCREENWASH CONCENTRATE

DNEL Workers - Inhalation; Long term systemic effects: 0.201 mg/m³

Workers - Dermal; Long term systemic effects: 0.0569 mg/kg bw/day

Workers - Dermal; Long term local effects: 0.41 mg/cm² Workers - Dermal; Short term Acute: 0.41 mg/cm²

General population - Inhalation; Long term systemic effects: 0.0593 mg/m³ General population - Inhalation; Long term local effects: 0.0593 mg/m³

General population - Dermal; Long term systemic effects: 0.0342 mg/kg bw/day

General population - Dermal; Short term Acute: 0.205 mg/cm² General population - Dermal; Long term local effects: 0.41 mg/cm²

General population - Oral; Long term systemic effects: 0.0342 mg/kg bw/day

General population - Oral; Short term Acute: 0.205 mg/kg bw/day

PNEC - Fresh water; 0.00204 mg/l

Marine water; 0.000204 mg/lIntermittent release; 0.0204 mg/l

- STP; 1.049 mg/l

- Soil; 0.0463 mg/kg soil dw

PARA-MENTH-1-EN-8-OL (CAS: 98-55-5)

DNEL No DNEL available.

PNEC - STP; 2.6 mg/l

PNEC

Sediment (Freshwater); 1.85 mg/kgSediment (Marinewater); 0.185 mg/kg

- Soil; 0.329 mg/kg

CITRONELLOL (CAS: 106-22-9)

DNEL Workers - Inhalation; Long term systemic effects: 161.6 mg/m³

Workers - Inhalation; Long term local effects: 10 mg/m³ Workers - Inhalation; Short term Acute: 10 mg/m³

Workers - Dermal; Long term systemic effects: 327.4 mg/kg bw/day General population - Inhalation; Long term systemic effects: 47.8 mg/m³ General population - Inhalation; Long term local effects: 10 mg/m³

General population - Inhalation; Short term Acute: 10 mg/m³

General population - Dermal; Long term systemic effects: 196.4 mg/kg bw/day General population - Dermal; Short term local effects, Acute: 2.950 mg/cm²

Workers - Dermal; Short term Acute, local effects: 2.950 mg/cm²

General population - Oral; Long term systemic effects: 13.8 mg/kg bw/day

Fresh water; 0.0024 mg/l

Marine water; 0.00024 mg/lIntermittent release; 0.024 mg/l

- STP; 580 mg/l

Sediment (Freshwater); 0.0256 mg/kg sediment dw
Sediment (Marinewater); 0.00256 mg/kg sediment dw

- Soil; 0.00371 mg/kg soil dw

Nerol (CAS: 106-25-2)

UNIPART SCREENWASH CONCENTRATE

DNEL Workers - Inhalation; Long term systemic effects: 5.4 mg/m³

Workers - Dermal; Long term systemic effects: 0.76 mg/kg bw/day

Workers - Dermal; Long term local effects: 0.133 mg/cm²

General population - Inhalation; Long term systemic effects: 1.3 mg/m³ General population - Dermal; Long term systemic effects: 0.38 mg/kg bw/day General population - Oral; Long term systemic effects: 0.38 mg/kg bw/day

PNEC - Fresh water; 0.00745 mg/l

Marine water; 0.000745 mg/lIntermittent release; 0.0745 mg/l

- STP; 12.9 mg/l

Sediment (Freshwater); 0.133 mg/kg sediment dwSediment (Marinewater); 0.0133 mg/kg sediment dw

- Soil; 0.0223 mg/kg soil dw

CINNAMYL ALCOHOL (CAS: 104-54-1)

DNEL Workers - Inhalation; Long term systemic effects: 2.277 mg/m³

Workers - Dermal; Long term systemic effects: 1.998 mg/kg bw/day

General population - Inhalation; Long term systemic effects: 0.5665 mg/m³ General population - Dermal; Long term systemic effects: 0.4926 mg/kg bw/day General population - Oral; Long term systemic effects: 3.995 mg/kg bw/day

PNEC - Fresh water; 0.109 mg/l

Marine water; 0.0109 mg/lIntermittent release; 1.09 mg/l

- STP; 16.127 mg/l

Sediment (Freshwater); 220.188 mg/kg sediment dwSediment (Marinewater); 220.188 mg/kg sediment dw

- Soil; 0.185 mg/kg soil dw

BENZYL VIOLET 4B (CAS: 1694-09-3)

DNEL No DNEL available.

PNEC No PNEC available.

Decanal (CAS: 112-31-2)

DNEL Workers - Inhalation; Long term systemic effects: 24.9 mg/m³

Workers - Dermal; Long term systemic effects: 7 mg/kg bw/day

General population - Inhalation; Long term systemic effects: 6.1 mg/m³ General population - Dermal; Long term systemic effects: 3.5 mg/kg bw/day General population - Oral; Long term systemic effects: 3.5 mg/kg bw/day

PNEC - Fresh water; 0.00117 mg/l

- Marine water; 0.000117 mg/l

- Intermittent release; 0.0117 mg/l

- STP; 3.16 mg/l

- Sediment (Freshwater); 0.0972 mg/kg sediment dw

- Sediment (Marinewater); 0.00972 mg/kg sediment dw

- Soil; 0.0187 mg/kg soil dw

Octanal (CAS: 124-13-0)

DNEL Workers - Inhalation; Long term systemic effects: 1.3 mg/m³

Workers - Dermal; Long term systemic effects: 0.37 mg/kg bw/day General population - Inhalation; Long term systemic effects: 0.32 mg/m³ General population - Dermal; Long term systemic effects: 0.19 mg/kg bw/day General population - Oral; Long term systemic effects: 0.19 mg/kg bw/day

PNEC - Fresh water; 0.00154 mg/l

- Marine water; 0.000154 mg/l

- STP; 3.16 mg/l

Sediment (Freshwater); 0.07146 mg/kg sediment dw
Sediment (Marinewater); 0.00715 mg/kg sediment dw

- Soil; 0.01339 mg/kg soil dw

4-(2,6,-TRIMETHYLCYCLOHEX-1-ENE-1-YL)-BUT-3-ENE-2-ONE (CAS: 14901-07-6)

DNEL Workers - Inhalation; Long term systemic effects: 23.21 mg/m³

Workers - Dermal; Long term systemic effects: 13.17 mg/kg bw/day General population - Inhalation; Long term systemic effects: 5.72 mg/m³ General population - Dermal; Long term systemic effects: 6.58 mg/kg bw/day General population - Oral; Long term systemic effects: 3.29 mg/kg bw/day

PNEC - Fresh water; 0.004146 mg/l

Marine water; 0.0004146 mg/lIntermittent release; 0.04146 mg/l

- STP; 0.698 mg/l

Sediment (Freshwater); 63.23 mg/kg sediment dwSediment (Marinewater); 63.23 mg/kg sediment dw

- Soil; 29.47 mg/kg soil dw

BENZYLOXYMETHANOL (CAS: 14548-60-8)

DNELNo DNEL available.PNECNo PNEC available.

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles. Contact lenses should not be worn when working with this chemical.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: In case of intensive contact, wear protective gloves (EN 374). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. protective gloves shall be replaced immediately when physically damaged or worn. Appropriate Material - Butyl, Material Thickness - 0.6 to 0.8mm, Breakthrough Time - 8Hrs

UNIPART SCREENWASH CONCENTRATE

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent

absorption through the skin.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide

eyewash station.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respiratory

fitted with the following cartridge: Gas filter, type A2.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Coloured liquid.

Colour Blue.

Odour Alcoholic. Perfume.

pH 6.5 to 8.5 **Melting point** < -16.0°C

Initial boiling point and range Approximately 95°C @ 760 mm Hg

Flash point 40°C CC (Closed cup).

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 6.0% v/v METHANOL IN AIR Upper flammable/explosive

limit: 36.5% v/v METHANOL IN AIR

Relative density 0.980 @ 20°C

Solubility(ies) Completely soluble in water. Very soluble in the following materials: Alcohols.

Comments Information given is applicable to the product as supplied.

9.2. Other information

Refractive index 1.339 @ 20°C

Volatile organic compound This product contains a maximum VOC content of 140.0 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not applicable. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.

UNIPART SCREENWASH CONCENTRATE

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 1,881.47

Acute toxicity - dermal

ATE dermal (mg/kg) 6,754.47

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 67.54

General information To the best of our knowledge the chemical, physical and toxicological properties have not

been thoroughly investigated.

Inhalation Harmful: possible risk of irreversible effects through inhalation. Vapours may irritate

throat/respiratory system. Symptoms following overexposure may include the following: Headache. Dizziness. Drowsiness. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea,

vomiting.

Ingestion Harmful: possible risk of irreversible effects if swallowed. May cause nausea, headache,

dizziness and intoxication. Ingestion of large amounts may cause headaches, nausea, vomiting, abdominal pain, drowsiness and unconciousness. Methanol can cause blindness

when ingested.

Skin contact Harmful: possible risk of irreversible effects in contact with skin. Contains components which

may penetrate the skin. Product has a defatting effect on skin. Repeated exposure may cause

skin dryness or cracking. May cause allergic contact eczema.

Eye contact May cause temporary eye irritation.

Acute and chronic health

hazards

Not expected to be a health hazard when used under normal conditions. Risk of long-term effects is considered to be minimal from exposure to concentrations below the level of OEL. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Central and/or peripheral nervous system damage. Brain damage.

Route of entry Inhalation Ingestion. Skin absorption

Target organs Central nervous system Eyes Gastro-intestinal tract Kidneys Liver Respiratory system, lungs

Blood

Medical symptoms Symptoms overexposure may include the following: Nausea, vomiting. Severe

stomach pain. Central nervous system depression. Blindness. Unconsciousness, possibly

death.

Medical considerations Irritation of eyes and mucous membranes. Central nervous system depression. Drowsiness,

dizziness, disorientation, vertigo. Visual disturbances, including blurred vision.

Toxicological information on ingredients.

METHANOL

UNIPART SCREENWASH CONCENTRATE

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

Species Rat

Notes (oral LD₅₀) Toxic if swallowed.

300.0 ATE oral (mg/kg)

Acute toxicity - dermal

Acute toxicity dermal (LD50

mg/kg)

15,800.0

5,628.0

Species Rabbit

Notes (dermal LD50) Toxic in contact with skin.

ATE dermal (mg/kg) 1,000.0

Acute toxicity - inhalation

Acute toxicity inhalation

83.2

10.0

(LC50 vapours mg/l)

Species Rat

Notes (inhalation LC₅₀) Toxic if inhaled.

ATE inhalation (vapours

mg/l)

Skin corrosion/irritation

Animal data Not irritating.

Serious eye damage/irritation

Serious eye

Not irritating.

damage/irritation

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro This substance has no evidence of mutagenic properties. Negative.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity -

Fertility: - NOAEC 1.3 mg/l, , Rat Based on available data the classification criteria

fertility are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Causes damage to organs .

Target organs Central nervous system Optic Nerve (Nervus Opticus)

UNIPART SCREENWASH CONCENTRATE

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazardBased on available data the classification criteria are not met.

.

Inhalation Toxic by inhalation. Possible effects include headache, dizziness, cramp, nausea,

vomiting, blindness, unconsciousness and death. Danger of very serious irriversible

effects.

Ingestion Toxic if swallowed. Possible effects include headache, dizziness, nausea, vomiting,

cramp, blindness, unconsciousness and death. There is danger of very serious and

irriversible effects if swallawed.

Skin contact Toxic in contact with skin. Danger of serious irreversible effects.

ETHANEDIOL

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

7,712.0

Species Rat

Notes (oral LD₅₀) Acute oral toxicity is expected to be moderate in humans eventhough animals test

results would suggest a low toxicity. Ingestion of approximately 100ml has caused death in humans. Ingestion may cause nausea, vomiting, abdominal discomfort or

diarrhea. Excessive exposure may cause central nervous system effects,

cardiopulmonary effects and kidney failure.

ATE oral (mg/kg) 500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 3,501.0

mg/kg)

Species

Mouse

ATE dermal (mg/kg) 3,501.0

Acute toxicity - inhalation

Acute toxicity inhalation

(LC₅₀ vapours mg/l)

2.6

Species Rat

Notes (inhalation LC₅₀) At room temperature exposure to vapour is minimal due to low volatility. With good

ventilation single exposure is not expected to cause adverse effect. If the product is heated or the working area has poor ventilation, vapour/mist may accumulate and

cause respiratory irritation and symptoms such as headache and nausea.

Skin corrosion/irritation

Animal data Not irritating. Rabbit

Serious eye damage/irritation

Serious eye Not irritating. Rabbit

damage/irritation

UNIPART SCREENWASH CONCENTRATE

Respiratory sensitisation

Respiratory sensitisation Guinea pig: Not sensitising.

Skin sensitisation

Skin sensitisation - Guinea pig: Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

Carcinogenicity The current toxicological kowledge allows to not classify the product as a

carcinogen.

Reproductive toxicity

Reproductive toxicity -

fertility

Ingestion of large amounts has been shown to interfere with reproduction in

animals.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Observations in humans include: Nystagmus (involuntary eye movement). In

animals effects have been reported on the following organs: kidneys and liver.

NOAEL 150 mg/kg/day, Oral, Rat

Target organs Kidneys

Inhalation At room temperature, exposure to vapor is minimal due to low volatility. With good

ventilation, single exposure is not expected to cause adverse effects. If material is heated or areas are poorly ventilated, vapor/mist may accumulate and cause

respiratory irritation and symptoms such as headache and nausea.

Ingestion Oral toxicity is expected to be moderate in humans due to ethylene glycol even

though tests with animals show a lower degree of toxicity. Ingestion of quantities (approximately 65 mL (2 oz.) for diethylene glycol or 100 mL (3 oz.) for ethylene glycol) has caused death in humans. May cause nausea and vomiting. May cause abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure. For Ethylene glycol: Lethal Dose, Human, adult 100 ml LD50, rat, male and female

7,712 mg/kg.

Skin contact Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Repeated skin exposure to large quantities may result in absorption of harmful amounts. Massive contact with damaged skin or of material sufficiently hot to burn

skin may result in absorption of potentially lethal amounts.

Eye contact May cause temporary eye irritation.

Route of entry Ingestion.

Target organs Kidneys Liver

SECTION 12: Ecological Information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or

frequent spills may have hazardous effects on the environment.

12.1. Toxicity

UNIPART SCREENWASH CONCENTRATE

Toxicity Not considered toxic to fish.

Ecological information on ingredients.

METHANOL

Acute toxicity - fish LC50, 96 hours: 15400 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours, 48 hours: > 10000 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅o, 96 hours: ~ 22000 mg/l, Pseudokirchneriella subcapitata

ETHANEDIOL

Toxicity Product not classified as dangerous to aquatic organisms.

Acute toxicity - fish LC50, 96 hours, 96 hours: 72860 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours, 48 hours: > 100 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 96 hours, 96 hours: 6500 - 13000 mg/l, Selenastrum capricornutum

Acute toxicity -

microorganisms

EC20, 30 min, 30 minutes: > 1995 mg/l, Activated sludge

life stage

Chronic toxicity - fish early NOEC, 7 days: 15380 mg/l, Pimephales promelas (Fat-head Minnow)

Chronic toxicity - aquatic

invertebrates

NOEC, 7 days: 8590 mg/l, Ceriodaphnia Sp.

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable but it must not be discharged into drains without permission from the authorities. The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request, or at the request of a detergent manufacturer.

Ecological information on ingredients.

METHANOL

Biodegradation The substance is readily biodegradable.

ETHANEDIOL

Persistence and degradability

The product is biodegradable.

Biodegradation - Degradation (%) 90 - 100%: 10 days

> Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% biodegradation in OECD test(s) for inherent

biodegradability).

12.3. Bioaccumulative potential

UNIPART SCREENWASH CONCENTRATE

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Ecological information on ingredients.

METHANOL

Bioaccumulative potential Not potentially bioaccumulative

Partition coefficient : -0.77

ETHANEDIOL

Bioaccumulative potential Not potentially bioaccumulative

Partition coefficient log Pow: -1.36

12.4. Mobility in soil

Mobility The product is soluble in water.

Ecological information on ingredients.

METHANOL

Mobility The product is soluble in water. The product contains volatile organic compounds

(VOCs) which will evaporate easily from all surfaces.

ETHANEDIOL

Mobility The product is soluble in water. Volatilization from natural bodies of water or moist

soil is not expected to be an important fate process. Potential for mobility in soil is

very high.

Adsorption/desorption

coefficient

Soil - Koc: ~ 1 @ °C

Henry's law constant ~ 8.05E-09 atm m3/mol @ 25°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvBThis product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

METHANOL

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

ETHANEDIOL

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

Other adverse effects Not applicable.

Ecological information on ingredients.

METHANOL

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority. The packaging must

be empty (drop-free when inverted).

Disposal methodsAbsorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a

licensed waste disposal contractor. Containers should be thoroughly emptied before disposal

because of the risk of an explosion.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993 UN No. (IMDG) 1993 UN No. (ICAO) 1993 UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (CONTAINS METHANOL)

Proper shipping name

(IMDG)

FLAMMABLE LIQUID, N.O.S. (CONTAINS METHANOL)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (CONTAINS METHANOL)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (CONTAINS METHANOL)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ADN packing group III

ICAO packing group III

UNIPART SCREENWASH CONCENTRATE

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

30

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Pollution (Special Waste) Regulations 1980 (as amended).

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Issued by HS&E Manager.

Revision date 11/01/2016

Revision 4

Supersedes date 27/05/2015

SDS status Approved.

UNIPART SCREENWASH CONCENTRATE

Risk phrases in full R10 Flammable.

R11 Highly flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R22 Harmful if swallowed.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact

with skin and if swallowed.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

H370 Causes damage to organs (Central nervous system, Optic Nerve (Nervus Opticus)). H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure if

swallowed.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.