

Printing date 15.03.2013 Revision: 14.01.2013

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: SabaPVC 2810
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the preparation Adhesive
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SABA Dinxperlo BV

Industriestraat 3

NL-7091 DC Dinxperlo

The Netherlands

P.O Box 3

NL - 7090 AA Dinxperlo

The Netherlands

Tel.: +31 315 65 89 99 Fax: +31 315 65 32 07 E-mail: info@saba.nl Internet: www.saba.nl

- · Further information obtainable from: Drs. J.W. Diesveld (e-mail: j.diesveld@saba.nl)
- · Emergency telephone number: Tel.: +31 315 65 89 99

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36: Irritating to eyes.

*

R66-67:

F; Highly flammable

dizziness.

R11: Highly flammable.

Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Printing date 15.03.2013 Revision: 14.01.2013

Trade name: SabaPVC 2810

(Contd. of page 1)

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Xi Irritant

F Highly flammable

· Risk phrases:

- 11 Highly flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compon	ents:	
CAS: 78-93-3	butanone	58.76%
EINECS: 201-159-0	🗶 Xi R36; 🙀 F R11	
	R66-67	
	🊸 Flam. Liq. 2, H225; ∿ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 141-78-6	ethyl acetate	26.89%
EINECS: 205-500-4	X i R36; → F R11	
	R66-67	
	🊸 Flam. Liq. 2, H225; ∿ Eye Irrit. 2, H319; STOT SE 3, H336	

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB

Printing date 15.03.2013 Revision: 14.01.2013

Trade name: SabaPVC 2810

(Contd. of page 2)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Hydrogen chloride (HCl)

Carbon monoxide and carbon dioxide

- · Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Keep people at a distance and stay on the windward side.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 15.03.2013 Revision: 14.01.2013

Trade name: SabaPVC 2810

(Contd. of page 3)

· Control parameters

78-93-3 butanone WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

· Ingredients with limit values that require monitoring at the workplace:

Sk, BMGV

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm Long-term value: 200 ppm

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L

Medium: urine Sampling time: post shift

Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Short term filter device:

Filter A

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Neoprene gloves

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

Printing date 15.03.2013 Revision: 14.01.2013

Trade name: SabaPVC 2810

(Contd. of page 4)

Information on basic physica	al and chamical proporties
General Information	u ana cnemicai properiies
Appearance:	
Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
pH-value:	Not applicable.
Change in condition Boiling point/Boiling rang	e: 77 °C
Flash point:	-4 °C
Flammability (solid, gaseous): Not applicable.
Ignition temperature:	450 °C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.8 Vol %
Upper:	11.5 Vol %
Vapour pressure at 20 °C:	105 hPa
Density at 20 °C:	0.88 g/cm^3
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
	The master of alfred to man
Viscosity: Dynamic at 20 °C:	70 mPas
Solvent content:	
Organic solvents:	85.5 %
VOC (EC)	85.77 %
Solids content:	14.5 %
Other information	The physical data presented above are typical values and should not

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Decomposes with water, acids and alkalis.

Violent reactions with strong alkalis and oxidizing agents.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Hydrogen chloride (HCl)

Carbon monoxide and carbon dioxide

Printing date 15.03.2013 Revision: 14.01.2013

Trade name: SabaPVC 2810

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:				
78-93-3 butanone				
Oral	LD50	>2500 mg/kg (rat)		
Dermal	<i>LD50</i>	>5000 mg/kg (rabbit)		
Inhalative	LC50/4 h	20 mg/l (rat)		
141-78-6 е	141-78-6 ethyl acetate			
Oral	LD50	4100 mg/kg (mouse)		
		10170 mg/kg (rat)		
		4935 mg/kg (rabbit)		
Dermal	<i>LD50</i>	> 18000 mg/kg (rabbit)		
Inhalative	LC50/4 h	31.0 mg/l (mouse)		
		> 50 mg/l (rat)		

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

78-93-3 butanone

EC50 | 12600 mg/kg (daphnia)

141-78-6 ethyl acetate

EC50 > 164 mg/kg (daphnia)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

GB

Printing date 15.03.2013 Revision: 14.01.2013

Trade name: SabaPVC 2810

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number	
ADR, IMDG, IATA	UN1133
UN proper shipping name	
ADR	1133 ADHESIVES, special provision 640D
IMDG, IATA	ADHESIVES
Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3 (F1) Frammable tiquias.
IMDG, IATA	
3	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F- E , S - D
Transport in bulk according to Annex	x II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Excepted quantities (EQ):	E2
Limited quantities (LQ)	5L
Transport category	2
Tunnel restriction code	D/E

(Contd. on page 8)

Printing date 15.03.2013 Revision: 14.01.2013

Trade name: SabaPVC 2810

(Contd. of page 7)

· UN "Model Regulation": UN1133, ADHESIVES, special provision 640D, 3, II

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

R11 Highly flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· Contact: Drs. J.W. Diesveld

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

GB