

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 1 of 11
Language: en-IE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

This safety data sheet pertains to the following products:

BLOCK BOND® FAST HOOF ADHESIVE Isocyanate / KLAUENKLEBSTOFF Isocyanat,
UFI: NE20-30YC-E00R-C2DF

BLOCK BOND® SEMI FAST HOOF ADHESIVE Isocyanate / KLAUENKLEBSTOFF Isocyanat,
UFI: X050-90P8-M00K-69VD

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Isocyanate component for a 2-component adhesive
Reserved for industrial and professional use.

Uses advised against: Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Company name: WIKO Klebetechnik Sp. z o.o.
Street/POB-No.: ul. Ekonomiczna 8
Postal Code, city: PL-42-271 Częstochowa
WWW: www.gluetec-group.com
E-mail: info.pl@gluetec-group.com
Telephone: +48 (0) 34 372 58 58
Telefax: +48 (0) 34 371 11 14

Department responsible for information:
Telephone: +48 (0) 34 372 58 58, E-mail: info.pl@gluetec-group.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen, Germany,
Telephone: +49 551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Acute Tox. 4; H332 Harmful if inhaled.

Skin Sens. 1; H317 May cause an allergic skin reaction.

STOT SE 3; H335 May cause respiratory irritation.

2.2 Label elements

Labelling (CLP)



Signal word:

Warning

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2 Revision date: 3/12/2024 Page: 2 of 11
Replaces version: 2.1 Date of print: 31/1/2025 Language: en-IE

Hazard statements:	H317	May cause an allergic skin reaction.
	H332	Harmful if inhaled.
	H335	May cause respiratory irritation.
Precautionary statements:	P261	Avoid breathing mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection.
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P312	Call a POISON CENTER/doctor if you feel unwell.
	P362+P364	Take off contaminated clothing and wash it before reuse.
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Special labelling

Text for labelling:	EUH204	Contains isocyanates. May produce an allergic reaction.
	Contains:	
	Hexamethylene-1,6-di-isocyanate homopolymer	
	Hexamethylene-1,6-di-isocyanate	

2.3 Other hazards

Special danger of slipping by leaking/spilling product.
Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

Endocrine disrupting properties, Results of PBT and vPvB assessment:
This mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% (w/w) or higher.
The product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119485796-17-xxxx list no. 931-274-8 CAS 28182-81-2	Hexamethylene-1,6-di-isocyanate homopolymer Acute Tox. 4; H332. Skin Sens. 1; H317. STOT SE 3; H335.	90 - 100 %
REACH 01-2119457571-37-xxxx EC No. 212-485-8 CAS 822-06-0	Hexamethylene-1,6-di-isocyanate Acute Tox. 4; H302. Acute Tox. 1; H330. Skin Irrit. 2; H315. Eye Irrit. 2; H319. Resp. Sens. 1; H334. Skin Sens. 1; H317. STOT SE 3; H335. Specific concentration limits (SCL): Skin Sens. 1; H317: C ≥ 0.5 % Resp. Sens. 1; H334: C ≥ 0.5 %	< 0.1 %

Full text of H- and EUH-statements: see section 16.

Additional information: Contains silicon dioxide.
The maximum workplace exposure limits are, where necessary, listed in section 8.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 3 of 11
Language: en-IE

SECTION 4: First aid measures

4.1 Description of first aid measures

- General information: If medical advice is needed, have product container or label at hand. Take off immediately all contaminated clothing and wash it before reuse.
- In case of inhalation: Move victim to fresh air; if necessary, provide artificial respiration or oxygen. If victim is at risk of losing consciousness, position and transport on their side. Seek medical attention.
- Following skin contact: After contact with skin, wash immediately with soap and plenty of water.
In case of skin reactions, consult a physician.
- After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.
Consult an ophthalmologist.
- After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. Harmful if inhaled. May cause respiratory irritation. Delayed occurrence of discomfort and development of hypersensitivity are possible even at low concentrations of isocyanates.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. First Aid, Decontamination.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray jet, extinguishing powder, foam, carbon dioxide.

Extinguishing media which must not be used for safety reasons:
Full water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. In case of fire may be liberated: toxic gases/vapours, Isocyanate vapours, traces of hydrogen cyanide, nitrous fumes, carbon monoxide, carbon dioxide. Air combined with vapours may form potentially explosive mixtures that are heavier than air.

5.3 Advice for firefighters

- Special protective equipment for firefighters: Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.
- Additional information: Heating will lead to pressure increase: Danger of bursting and explosion. Use fine water spray to cool endangered containers.
Move undamaged containers from immediate hazard area if it can be done safely.
Do not allow fire water to penetrate into surface or ground water.
Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 4 of 11
Language: en-IE

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with the substance. Avoid breathing mist/vapours/spray. Wear appropriate protective equipment. Provide for sufficient ventilation, particularly in closed rooms. Keep unprotected people away. Take off immediately all contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains.
In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Cover with moist liquid binding material (e.g. sand, chemical agent with calcium silicahydrate). After approximately 1 hour, mechanically collect in an open waste container (CO₂ build-up). keep moist and allow to stand in a secure area for 7 to 14 days.
Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information:

Remove all sources of ignition.
Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling:

Provide adequate ventilation, and local exhaust as needed.
Avoid the formation of aerosol. Avoid breathing mist/vapours/spray.
Avoid contact with skin and eyes. Take off immediately all contaminated clothing and wash it before reuse. Keep work clothes separately.
When using do not eat, drink or smoke. Wear appropriate protective equipment. Wash hands before breaks and after work. Protect skin by using skin protective cream. Persons with over-sensitive breath ways (e.g. asthma, chronic bronchitis) are not allowed to use the product due to safety regulations.

Precautions against fire and explosion:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take action to prevent static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position.
Suitable material for containers/equipment: aluminium, steel, refined steel
Unsuitable container/equipment material: copper, tin
Only use containers specifically approved for the substance/product.
Flexible containers: Store under protective gas (nitrogen).

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 5 of 11
Language: en-IE

Hints on joint storage: Do not store together with combustible or self-igniting materials or any highly flammable solids.
keep away from: Water, acids, alkalis, amines, alcohols.
Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
28182-81-2	Hexamethylene-1,6-di-isocyanate homopolymer	Europe: BOELV: STEL	20 µg/m ³ (may be absorbed through the skin)
		Europe: BOELV: TWA	10 µg/m ³ (may be absorbed through the skin)
		Ireland: 15 minutes Ireland: 8 hours	0.07 mg/m ³ 0.02 mg/m ³
822-06-0	Hexamethylene-1,6-di-isocyanate	Ireland: 8 hours	0.005 ppm
112945-52-5	Silicon dioxide	Ireland: 8 hours	2.4 mg/m ³ (Silicon dioxide, amorphous, respirable fraction)
		Ireland: 8 hours	6 mg/m ³ (Silicon dioxide, amorphous, inhalable fraction)

DNEL/DMEL:

Information about Hexamethylene-1,6-di-isocyanate-homopolymer:
DNEL long-term, workers, inhalative, local: 0.5 mg/m³
DNEL short-term, workers, inhalative, local: 1 mg/m³

PNEC:

Information about Hexamethylene-1,6-di-isocyanate-homopolymer:
PNEC water (freshwater): 0.127 mg/L
PNEC sediment (freshwater): 266,701 mg/kg dw
PNEC water (marine water): 0.0127 mg/L
PNEC sediment (marine water): 26,670 mg/kg dw
PNEC water (intermittent release): 1.27 mg/L
PNEC sewage treatment plant: 88 mg/L
PNEC soil: 53,183 mg/kg dw

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.
When aerosols and vapours form: Withdraw by suction.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 6 of 11
Language: en-IE

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. Respiratory protection: A2/P2 or better, depending on the operational load. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product.

Hand protection: Protective gloves according to I.S. EN ISO 374:1. Glove material: butyl caoutchouc (butyl rubber) - Layer thickness: > 0.5 mm Breakthrough time: > 480 min Glove material: fluoro rubber - Layer thickness: > 0.4 mm Breakthrough time: > 480 min Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to I.S. EN ISO 16321-1:2022.

Body protection: Wear suitable protective clothing.

General protection and hygiene measures: Persons with over-sensitive breath ways (e.g. asthma, chronic bronchitis) are not allowed to use the product due to safety regulations. Avoid contact with skin, eyes, and clothing. Take off immediately all contaminated clothing and wash it before reuse. Avoid breathing mist/vapours/spray. Wash hands before breaks and after work. When using do not eat, drink or smoke. Work place should be equipped with a shower and an eye rinsing apparatus.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	Form: Pasty colourless
Odour:	almost odourless
Odour threshold:	Not determined
Melting point/freezing point:	approx. - 51 °C" (Hexamethylene-1,6-di-isocyanate homopolymer)
Initial boiling point and boiling range:	Not applicable, Decomposition
Flammability:	No data available
Upper/lower flammability or explosive limits:	No data available
Flash point/flash point range:	approx. 223 °C" (Hexamethylene-1,6-di-isocyanate homopolymer)
Decomposition temperature:	approx. 250 °C" (Hexamethylene-1,6-di-isocyanate homopolymer)
pH:	Not applicable
Viscosity, kinematic:	No data available
Water solubility:	at 15 °C: Immiscible
Partition coefficient: n-octanol/water:	No data available
Vapour pressure:	at 20 °C: 0.007 hPa (Hexamethylene-1,6-di-isocyanate) at 20 °C: <= 0.00003 hPa (Hexamethylene-1,6-di-isocyanate homopolymer)
Density:	at 20 °C: approx. 1.17 g/mL (Hexamethylene-1,6-di-isocyanate homopolymer (DIN 53217))
Vapour density:	No data available
Particle characteristics:	Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 7 of 11
Language: en-IE

9.2 Other information

Explosive properties:	No data available
Oxidizing characteristics:	No data available
Auto-ignition temperature:	No data available
Evaporation rate:	No data available
Additional information:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms carbon dioxide and turns into a hard and insoluble by-product (poly urea) on the water's edge.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Exothermic reactions with: Water, alcohols, amines, bases.
Formation of Carbon dioxide. Danger of bursting of closed cans.

10.4 Conditions to avoid

Keep away from sources of ignition - No smoking. Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

10.5 Incompatible materials

Water, acids, alkalis, amines, alcohols

10.6 Hazardous decomposition products

Exothermal decomposition with formation of: toxic gases/vapours, nitrogen oxides (NO_x), carbon monoxide and carbon dioxide.

Thermal decomposition: approx. 250 °C" (Hexamethylene-1,6-di-isocyanate homopolymer)

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 8 of 11
Language: en-IE

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects:

The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

ATEmix (calculated): $2,000 < ATE < 5,000$ mg/kg.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

ATEmix (calculated): $2,000 < ATE < 5,000$ mg/kg.

Acute toxicity (inhalative): Acute Tox. 4; H332 = Harmful if inhaled.

ATEmix (calculated): $1 < ATE < 5$ mg/L/4h (dust/vapours).

Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Skin Sens. 1; H317 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Genotoxicity, in-vivo: Micronucleus test; Mouse: negative (OECD 474)

Effects on or via lactation: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure): STOT SE 3; H335 = May cause respiratory irritation.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

11.2 Information on other hazards

Endocrine disrupting properties:

None

Other information:

Information about Hexamethylene-1,6-di-isocyanate homopolymer:

LD50 rat, oral: $> 2,000$ mg/kg (OECD 423)

LD50 Rabbit, dermal: $> 2,000$ mg/kg (OECD 402)

LC50 rat, inhalative (dust/mist): 1.5 mg/l (Data obtained by expert judgement.)

General remarks

Delayed occurrence of discomfort and development of hypersensitivity are possible even at low concentrations of isocyanates.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Information about Hexamethylene-1,6-di-isocyanate homopolymer:

Fish toxicity:

LC50 Danio rerio (zebrafish): > 100 mg/L/96 h (RL 67/548/EWG)

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): > 100 mg/L/48 h (RL 67/548/EWG)

Algae toxicity:

ErC50 Scenedesmus subspicatus: $> 1,000$ mg/L/72 h (RL 67/548/EWG)

Bacterial toxicity:

EC50 in activated sludge: $> 3,828$ mg/L/3 h (OECD 209, read across)

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 9 of 11
Language: en-IE

12.2 Persistence and degradability

Further details: Biodegradability:
Information about Hexamethylene-1,6-di-isocyanate homopolymer:
1 %/28 d, not easily bio-degradable (RL 67/548/EWG).

12.3 Bioaccumulative potential

Bioconcentration factor (BCF): Information about Hexamethylene-1,6-di-isocyanate homopolymer:
Bioconcentration factor (BCF): 3.2 (calculated)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The product does not contain any substances classified as PBT or vPvB.

12.6 Endocrine disrupting properties

None

12.7 Other adverse effects

General information: Forms carbon dioxide and turns into a hard and insoluble by-product (poly urea) on the water's edge. Based upon current knowledge, poly urea is inert and will not decompose. Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 08 05 01* = Waste isocyanates
* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation. Incinerate as hazardous waste according to applicable local, state, and federal regulations. Discharge into the environment must be avoided.

Package

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR: not applicable

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR: Not restricted

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 10 of 11
Language: en-IE

14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR: not applicable

14.4 Packing group

ADR/RID, IMDG, IATA-DGR: not applicable

14.5 Environmental hazards

Dangerous for the environment:

Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant: no

14.6 Special precautions for user

Protect from humidity. Sensitive to heat and warmth
Keep away from food, drink and animal feedingstuffs.
Von Säuren und Laugen fernhalten.

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - EC member states

Labelling of packaging with <= 125mL content



Signal word:

Warning

Hazard statements:

H317

May cause an allergic skin reaction.

EUH204

Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

P261

Avoid breathing mist/vapours/spray.

P280

Wear protective gloves/protective clothing/eye protection.

P362+P364

Take off contaminated clothing and wash it before reuse.

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3, 74, 75

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878



BLOCK BOND® FAST / SEMI FAST HOOF Isocyanate / KLAUENKLEBSTOFF Isocyanat

Material number HOOF-ADHESIVE-FAST-SEMIFAST_ISOCYANATE

Version: 2.2
Replaces version: 2.1

Revision date: 3/12/2024
Date of print: 31/1/2025

Page: 11 of 11
Language: en-IE

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H302 = Harmful if swallowed.
H315 = Causes skin irritation.
H317 = May cause an allergic skin reaction.
H319 = Causes serious eye irritation.
H330 = Fatal if inhaled.
H332 = Harmful if inhaled.
H334 = May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 = May cause respiratory irritation.
EUH204 = Contains isocyanates. May produce an allergic reaction.

Reason of change: Changes in section 8: Occupational exposure limit values

Date of first version: 6/10/2023

Department issuing data sheet:

see section 1: Department responsible for information

Abbreviations and acronyms: Acute Tox.: Acute toxicity
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
AS/NZS: Australian Standards/New Zealand Standards
BCF: Bioconcentration Factor
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EC50: Effective Concentration 50%
EN: European Standard
EQ: Excepted quantities
EU: European Union
Eye Irrit.: Eye irritation
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
LC50: Median lethal concentration
LD50: Lethal dose 50%
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
Resp. Sens.: Sensitisation to the respiratory tract
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Skin Irrit.: Skin irritation
Skin Sens.: Skin sensitisation
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at:
<http://sumdat.net/9wvghp3t>

