

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Dairy Spares Milking  
Machine Oil  
Page 1 of 5  
Number 250A  
Revision: 2  
18.08.04

## Safety data sheet

### 1. PRODUCT INFORMATION

Product Name Dairy Spares Milking Machine Oil  
Application Lubricant for Milking Machines and Vacuum pumps.  
Company **Morris Lubricants**  
Address **Castle Foregate, Shrewsbury, SY1 2EL, United Kingdom**  
Telephone No (+44) (0)1743 232200  
Fax No (+44) (0)1743 353584

### 2. COMPOSITION

| Name  | CAS No. | % Mass | Symbols/OEL | R Phrases |
|---|---------|--------|-------------|-----------|
| Severely refined mineral oil<br>(IP 346 DMSO extract <3%) | Mixture | >95    | OEL         | -         |

### 3. HAZARDS

This product is NOT classified as hazardous under current UK Health/Safety/Environmental Legislation, but should be handled in accordance with good industrial hygiene and safety practices.

Adverse Health Effects Repeated contact with the skin may result in skin irritation.

Other Hazards Large spills may cause contamination of soil and water.

### 4. FIRST AID MEASURES

Inhalation If inhalation of mist fumes or vapour causes irritation to the nose or throat or coughing remove to fresh air. If symptoms persist obtain medical advice.

Skin contact Remove contaminated clothing. Wash skin thoroughly using soap and water.

Eye contact Rinse with plenty of water (also under eyelids) for at least 10 minutes and seek medical attention if symptoms persist.

Ingestion Seek medical attention if discomfort continues.  
**DO NOT INDUCE VOMITING.**



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Paterson Enterprises Limited Shrewsbury

Registered in England No. 4930959



Certificate No. EMS 0044  
BS EN ISO14001 1996

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Dairy Spares Milking  
Machine Oil  
Page 2 of 5  
Number 250A  
Revision: 2  
18.08.04

## Safety data sheet

### 5. FIRE-FIGHTING MEASURES

Product not classified as flammable, but is inherently combustible.

|                                  |  |
|----------------------------------|--|
| Extinguishing Media              | Use carbon dioxide, foam or water spray. Prevent water used in spray from entering watercourses. |
| Not to be used                   | Direct water jet. Use water only to keep fire exposed containers cool.)                          |
| Special fire fighting procedures | In the event of a large fire self-contained breathing apparatus should be worn.                  |
| WARNING                          | Heat from a fire could possible result in drums bursting.  |

### 6. ACCIDENTAL RELEASE MEASURES

Contain and collect spillage with help of absorbent materials such as floor granules. Protect drains from potential spills to minimise contamination. If spillage enters drains call Environment Agency Emergency hotline on 0800 807060. Product should be disposed of according to Item 13.

### 7. HANDLING & STORAGE

|          |  |
|----------|--|
| Handling | Precautions should be taken against skin and eye contact. Avoid inhalation of vapour mist or fume. Do not wear contaminated clothing. Wear safety shoes when handling containers.  |
| Storage  | Store away from sources of strong heat and strong oxidising chemicals. Keep containers tightly closed in a cool dry, well ventilated place.<br>Take precautionary measures to prevent spills into drains, soil or water.<br>External tanks or stillage should be banded. |

### 8. EXPOSURE CONTROLS & PERSONAL PROTECTION

#### Engineering Measures

Ensure good ventilation. Use protective equipment and/or local ventilation when needed. Avoid skin contact and inhalation of oil mist.

#### Exposure Values

Comply with current local occupation exposure limit.  
It is recommended that mineral oil mists are kept below  $5\text{mg}/\text{m}^3$  (8hr T.W.A. value) EH40.

#### Protection and Hygiene

Wash hands before breaks and immediately after handling the product.  
Thoroughly clean contaminated skin and change dirty clothing and equipment.



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Paterson Enterprises Limited Shrewsbury

Registered in England No. 4930959



Certificate No. EMS 40644  
BS EN ISO14001 1996

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Dairy Spares Milking  
Machine Oil  
Page 3 of 5  
Number 250A  
Revision: 2  
18.08.04

## Safety data sheet

|                               |   |
|-------------------------------|---|
| <b>Respiratory Protection</b> | Oil Mist : respirator (combined particle and organic vapour filter type A2/P2)  |
| <b>Hand Protection</b>        | Protective gloves (PVC, Nitrile rubber) For further information consult glove manufacturer for recommendations of glove type associated with your particular application. So that break through times can be assessed. Show this data sheet |
| <b>Eye Protection</b>         | Safety goggles if there is a risk of splashing  |
| <b>Skin Protection</b>        | Protective clothing when needed.  |

### 9. PHYSICAL & CHEMICAL PROPERTIES: typical data

|                           |   |
|---------------------------|---|
| Appearance at 20°C        | Mobile liquid   |
| Odour                     | Mild  |
| pH                        | Neutral   |
| Density at 15°C           | 0.982 g/cm <sup>3</sup>                               |
| Viscosity at 40°C         | 77 cts  |
| Flash Point (ASTM D93)    | Greater than 180°C                                    |
| Auto-ignition temperature | Greater than 300°C                                    |
| Explosion Limits          | Not established                                       |
| Vapour pressure 20°C      | <0.1 kPa  |
| Solubility                | Insoluble in water.<br>Soluble in non-polar solvents. |

### 10. STABILITY & REACTIVITY

|  |  |
|--|--|
| Hazardous Reactions  | Products of this type are stable and unlikely to react in a hazardous manner under normal conditions of use. |
| Thermal Decomposition  | This material is combustible.  |
| Hazardous decomposition products, which can be formed on heating: Carbon monoxide, carbon dioxide, oxides of nitrogen and sulphur. |  |

### 11. TOXICOLOGICAL INFORMATION

|            |  |
|------------|--|
| Eyes       | Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.                                  |
| Skin       | Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated Exposure may lead to dermatitis. |
| Inhalation | At normal ambient temperatures is unlikely to cause inhalation hazard because of low volatility.                             |



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Paterson Enterprises Limited Shrewsbury

Registered in England No. 4930959



Certificate No. EMS 60044  
BS EN ISO14001 1996

# MORRIS

## LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Dairy Spares Milking  
Machine Oil  
Page 4 of 5  
Number 250A  
Revision: 2  
18.08.04

## Safety data sheet

- Ingestion Unlikely to cause harm if swallowed in small doses. Larger doses may cause nausea and diarrhoea.
- Other The refined mineral base oils used in this formulation are of low order of toxicity. LD50 (RAT) for base oil greater than 5g/kg.

### 12. ECOLOGICAL INFORMATION

- Mobility Some components may penetrate the soil causing ground water contamination.
- Degradability Inherently but not readily biodegradable.
- Bio accumulation No evidence to suggest bio-accumulation will occur.
- Aquatic toxicity Spills on water will form a film which may cause damage to organisms.

### 13. DISPOSAL CONSIDERATION

- Waste Send to a Registered Waste Disposal Site using the services of a Registered Waste Disposal Contractor. Ensure conformance with local and national regulations.
- Packaging Labels should not be removed from containers until they have been cleaned. Empty containers may contain hazardous residues. Ensure conformance with local and national regulations.
- Specific Advice As supplied material should be considered as Special Waste and Disposal should conform with the relevant Regulations.
- General Under no circumstances should this product be disposed of by putting into drains soil or water courses.

### 14. TRANSPORT INFORMATION

Not classified as Hazardous for Transport.

|                |     |                   |     |
|----------------|-----|-------------------|-----|
| U.N. Number:   | N/A | Packaging Group:  | N/A |
| Shipping Name: | N/A | Marine Pollutant: | No  |
| IMO Class:     | N/A | ICAO/IATA:        | N/A |
| ADR/RID:       | N/A |                   |     |



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Paterson Enterprises Limited Shrewsbury

Registered in England No. 4930959



Certificate No. EMS 00044  
BS EN ISO14001 1996

# MORRIS LUBRICANTS

Castle Foregate, Shrewsbury, Shropshire SY1 2EL  
Telephone (01743) 232200 Fax (01743) 353584  
www.morrislubricants.co.uk

Dairy Spares Milking  
Machine Oil  
Page 5 of 5  
Number 250A  
Revision: 2  
18.08.04

## Safety data sheet

### 15. REGULATORY INFORMATION

This product is NOT classified as hazardous for supply in the UK. No statutory label required.

|                       |   |
|-----------------------|---|
| Statutory Instruments | The Health & Safety at Work Act 1974.<br>Consumer Protection Act.<br>Environmental Protection Act.<br>COSHH Regulations CHIP Regulations. |
| Guidance              | COSHH Essentials CHIP for everyone  |

### 16. OTHER INFORMATION

Concave Report No. 5/87 Health Aspects of Lubricants.  
R Phases used in section 2 – none.

|                       |                |                      |
|-----------------------|----------------|----------------------|
| Original Issued date: | 03.03.94       |                      |
| Revision: 2           | Date: 18.08.04 | Change: All sections |

This information is, to the best of Paterson Enterprises Limited's knowledge, correct and is intended to describe the product requirements. Since the conditions of use are outside Paterson Enterprises Limited's control any recommendations or suggestions are made without guarantee and Paterson Enterprises Limited disclaims any liability for loss or damage suffered from use of this information. Customers must satisfy themselves that the product is suitable for a particular purpose. Furthermore, nothing contained herein shall be constructed as a recommendation to use any product in conflict with existing patents.



Certificate No. FM 21756  
BS EN ISO9001 2000

Established 1869

Morris Lubricants is a division of Paterson Enterprises Limited Shrewsbury

Registered in England No. 4930959



Certificate No. EMS 00044  
BS EN ISO14001 1996